
RD900 Series 191 Roller bering





Type	Brand	Weight	Outside Dia	Inner Dia	Total Height	External Bolt Circle Dia	Internal Bolt Circle Dia	Number Of Bolt Holes Per Hole Circle	Bolt Hole Dia	M	Number Of Grease Nipples	Diameter	Diameter	Ring Height	Ring Height	Distance At Bottom Outer Ring/Inner Ring	Distance At Bottom Outer Ring/Inner Ring	Gear P.C.D.	Module	Number Of Teeth	X.M	K.M	Tooth Width	Permissible Tangentialforces, Normal	Permissible tangentialforces, Maximum
		[KG]	Da [mm]	Di [mm]	H [mm]	La [mm]	Li [mm]	n	B [mm]	[mm]	n₁	O[mm]	U[mm]	H₁[mm]	H₂[mm]	Hu[mm]	Ho[mm]	d[mm]	M[mm]	Z	[mm]	[mm]	b[mm]	[kN]	[kN]
191.20.1250.990.41.1502	LYMC	542	1461,6	1103	132	1355	1155	36	26	24	3	1280	1282	106	123	9	26	1428	12	119	6	- 1,2	106	116,7	233,4
191.20.1400.990.41.1502	LYMC	646	1635,2	1253	132	1505	1305	36	26	24	3	1430	1432	106	123	9	26	1596	14	114	7	-1,4	106	136,2	272,4
191.20.1600.990.41.1502	LYMC	731	1831,2	1453	132	1705	1505	40	26	24	4	1630	1632	106	123	9	26	1792	14	128	7	- 1,4	106	136,2	272,4
191.20.1800.990.41.1502	LYMC	844	2044,8	1653	132	1905	1705	46	26	24	5	1830	1832	106	123	9	26	2000	16	125	8	- 1,6	106	155,6	311,2
191.20.2000.990.41.1502	LYMC	912	2236,8	1853	132	2105	1905	54	26	24	5	2030	2032	106	123	9	26	2192	16	137	8	- 1,6	106	155,6	311,2
191.25.1800.990.41.1502	LYMC	1126	2076,8	1619	147	1925	1685	36	33	30	6	1836	1826	117	138	9	30	2032	16	127	8	- 1,6	117	162,7	325,4
191.25.2000.990.41.1502	LYMC	1216	2268,8	1819	147	2125	1885	44	33	30	7	2036	2026	117	138	9	30	2224	16	139	8	- 1,6	117	162,7	325,4
191.25.2240.990.41.1502	LYMC	1378	2516,4	2059	147	2366	2125	48	33	30	8	2276	2266	117	138	9	30	2466	18	137	9	- 1,8	117	183,1	366,2
191.25.2500.990.41.1502	LYMC	1567	2786,4	2319	147	2625	2385	54	33	30	6	2536	2526	117	138	9	30	2736	18	152	9	- 1,8	117	183,1	366;2
191.25. 2800.990.41.1502	LYMC	1785	3096	2619	147	2925	2685	60	33	30	10	2836	2826	117	138	9	30	3040	20	152	10	- 2,0	117	203,4	406,8
191.32.2240.990.41 .1502	LYMC	1975	2552,4	2022	181	2395	2100	40	39	36	8	2281	2270	139	172	9	42	2502	18	139	9	- 1,8	139	217fj	435;2
191.32.2500.990 .41 .1502	LYMC	2260	2822,4	2282	181	2655	2360	44	39	36	7	2541	2530	139	172	9	42	2772	18	154	9	- 1,8	139	217{;	435,2
191.32.2800.990.41.1502	LYMC	2576	3136	2582	181	2955	2660	48	39	36	8	2841	2830	139	172	9	42	3080	20	154	10	- 2,0	139	241,7	483,4
191.32.3150.990.41.1502	LYMC	2828	3476	2882	181	3305	3010	56	39	36	7	3191	3180	139	172	9	42	3420	20	171	10	- 2,0	139	241,7	483,4
191.32.3550.990.41.1502	LYMC	3249	3889,6	3332	181	3705	3410	66	39	36	8	3591	3580	139	172	9	42	3828	22	174	11	- 2;2	139	265/J	531,8
191.32.4000.990 .41 .1502	LYMC	3752	4351,6	3782	181	4155	3860	72	39	36	9	4041	4030	139	172	9	42	4290	22	195	11	- 2;2	139	265/J	531,8
191.40.2800.990.41.1502	LYMC	3267	3136	2562	220	2965	2640	48	39	36	8	2850	2837	170	210	10	50	3080	20	154	10	- 2,0	170	295,7	591,4
191.40.3150 .990 .41.1502	LYMC	3812	3515,6	2912	220	3315	2990	56	39	36	7	3200	3187	170	210	10	50	3454	22	157	11	- 2,2	170	325,2	650,4
191.40.3550.990-41.1502	LYMC	4255	3911,6	3312	220	3715	3390	66	39	36	8	3600	3587	170	210	10	50	3850	22	175	11	- 2,2	170	325,2	650,4
191.40.4000.990.41.1502	LYMC	4805	4363,2	3762	220	4165	3840	72	39	36	9	4050	4037	170	210	10	50	4296	24	179	12	- 2,4	170	354,8	709,6
191.40.4500.990.41.1502	LYMC	5410	4867,2	4262	220	4665	4340	84	39	36	14	4550	4537	170	210	10	50	4800	24	200	12	- 2,4	170	354,8	709,6
191.50.3150.990.41.1502	LYMC	5298	3571,2	2885	268	3350	2975	48	45	42	8	3210	3196	203	258	10	65	3504	24	146	12	- 2,4	203	423,6	847;2
191.50.3550.990 .41.1502	LYMC	5830	3955,2	3285	268	3750	3375	54	45	42	9	3610	3596	203	258	10	65	3888	24	162	12	- 2,4	203	423,6	847;2
191.50.4000.990.41.1502	LYMC	6578	4411,2	3735	268	4200	3825	60	45	42	10	4060	4046	203	258	10	65	4344	24	181	12	- 2,4	203	423,6	847,2
191.50.4500.990.41.1502	LYMC	7456	4915,2	4235	268	4700	4325	68	45	42	11	4560	4546	203	258	10	65	4848	24	202	12	- 2,4	203	423,6	847,2
191.50.3150.990.41.1502	LYMC	5298	3571,2	2885	268	3350	2975	48	45	42	8	3210	3196	203	258	10	65	3504	24	146	12	- 2,4	203	423,6	847;2
191.50.3550.990 .41 .1502	LYMC	5830	3955,2	3285	268	3750	3375	54	45	42	9	3610	3596	203	258	10	65	3888	24	162	12	- 2,4	203	423,6	847;2
191.50.4000.990.41.1502	LYMC	6578	4411,2	3735	268	4200	3825	60	45	42	10	4060	4046	203	258	10	65	4344	24	181	12	- 2,4	203	423,6	847,2
191.50.4500.990.41.1502	LYMC	7456	4915,2	4235	268	4700	4325	68	45	42	11	4560	4546	203	258	10	65	4848	24	202	12	- 2,4	203	423,6	847,2
191.50.5000.990.41.1502	LYMC	8259	5419,2	4735	268	5200	4825	78	45	42	13	5060	5046	203	258	10	65	5328	24	222	24	- 2,4	203	423,6	847;2
191.50.5600 .990 .41.1502	LYMC	9448	6019,2	5335	268	5800	5425	90	45	42	15	5660	5646	203	258	10	65	5952	24	248	12	- 2,4	203	423,6	847;2
191 .50 .6300.990.41.1502	LYMC	10536	6715,2	6035	268	6500	6125	100	45	42	18	6360	6346	203	258	10	65	6624	24	276	24	- 2,4	203	423,6	847)
191.50.6735.990.41.1502	LYMC	11200	7147,2	6470	268	6935	6560	108	45	42	18	6795	6781	203	258	10	65	7080	24	295	12	- 2,4	203	423,6	847,2

LYMC BEARING