

KD210 series 231.20 281.30Type





Type	Brand	Weight	Ball Track Diameter	Outside Dia	Inner Dia	Total Height	External Bolt Circle Dia	Internal Bolt Circle Dia	Number Of Bolt Holes Per Hole Circle	Bolt Hole Dia	ni	B/M	t [mm]	Number Of Grease Nipples	Diameter	Diameter	Diameter	Diameter	Distance At Bottom Outer Ring/Inner Ring	Distance At Bottom Outer Ring/Inner Ring	Gear P.C.D.	Module	Number Of Teeth	Tooth Width	K.M	Permissible Tangentialforces, Normal	Permissible tangentialforces, Maximum	Bearing Clearance	
		[KG]	DL [mm]	Da [mm]	Di [mm]	H [mm]	La [mm]	Li [mm]	na	B/M [mm]		[mm]		n_1	O[mm]	U[mm]	A [mm]	C [mm]	Hu[mm]	Ho[mm]	d[mm]	M[mm]	Z	b[mm]	[mm]	[kN]	[kN]	Axial [mm]	Radial [mm]
231.20.0400.013 Typ 21/520.1	LYMC	29,3	414	504	304	56	455	332	10	M 12	12	18	20	4	412,5	415,5	-	375	10,5	-	495	5	99	45,5	-0,5	11,75	23,50	0,5	0,5
231.20.0500.013 Typ 21/650.1	LYMC	39,5	544	640,8	434	56	585	462	14	M 12	14	18	20	4	542,5	545,5	-	505	10,5	-	630	6	105	45,5	-0,6	14,20	28,40	0,5	0,5
231.20.0600.013 Typ 21/750.1	LYMC	47,6	644	742,8	534	56	685	562	16	M 12	16	18	20	4	642,5	645,5	-	605	10,5	-	732	6	122	45,5	-0,6	14,20	28,40	0.5	0,5
231.20.0700.013 Typ 21/850.1	LYMC	53,5	744	838,8	634	56	785	662	18	M 12	16	18	20	4	742,5	745,5	-	705	10,5	-	828	6	138	45,5	-0,6	14,20	28,40	0.5	0.5
231.20.0800.013 Typ 21/950.1	LYMC	65,1	844	950,4	734	56	885	762	18	M 12	18	18	20	4	842,5	845,5	-	805	10,5	-	936	8	117	45,5	- 0,8	18,93	37,86	0,5	0,5
231.20.0900.013 Typ 21/1050.1	LYMC	69,6	944	1046,4	834	56	985	862	20	M 12	20	18	20	4	942,5	945,5	-	905	10,5	-	1032	8	129	45,5	-0,8	18,93	37,86	0,5	0,5
231.20.1000.013 Typ 21/1200.1	LYMC	83,0	1094	l198,4	984	56	1135	1012	22	M 12	20	18	20	4	1092,5	1095,5	-	1055	10,5	-	1184	8	148	45,5	-0,8	18,93	37,86	0.5	0.5
231.21.0475.013 Typ 21/520.1	LYMC	29,3	414	504	305	56	455	332	10	M 12	12	18	20	4	412,5	412,5	-	375	5	-	495	5	99	45,5	-0,5	11,75	23,50	0 to 0.03	
231.21.0575.013 Typ 21/650.1	LYMC	39,5	544	640,8	435	56	585	462	14	M 12	14	18	20	4	542,5	542,5	-	505	6	-	630	6	105	45,5	-0,6	14,20	28,40	0 to 0.03	
231.21.0675.013 Typ 21/750.1	LYMC	47,6	644	742,8	535	56	685	562	16	M 12	16	18	20	4	642,5	642,5	-	605	6	-	732	6	122	45,5	-0,6	14,20	28,40	0 to 0.04	
231.21.0775.013 Typ 21/850.1	LYMC	53,5	744	838,8	635	56	785	662	18	M 12	16	18	20	4	742,5	742,5	-	705	6	-	828	6	138	45,5	-0,6	14,20	28,40	0 to 0.04	
231.21.0875.013 Typ 21/950.1	LYMC	65,1	844	950,4	735	56	885	762	18	M 12	18	18	20	4	842,5	842,5	-	805	8	-	936	8	117	45,5	- 0,8	18,93	37,86	0 to 0.05	
231.21.0975.013 Typ 21/1050.1	LYMC	69,6	944	1046,4	835	56	985	862	20	M 12	20	18	20	4	942,5	942,5	-	905	8	-	1032	8	129	45,5	-0,8	18,93	37,86	0 to 0.05	
231.21.1075.013 Typ 21/1200.1	LYMC	83,0	1094	l198,4	985	56	1135	1012	22	M 12	20	18	20	4	1092,5	1092,5	-	1055	8	-	1184	8	148	45,5	-0,8	18,93	37,86	0 to 0.06	
23_[]20.0400.503 Typ 21/520.1	LYMC	29,0	414	504	304	56	455	332	10	M 12	24	18	20	4	412.5	415,5	-	375	10,5	-	495	5	99	45,5	- 0.5	11.75	23,50	0,5	0,5
231.20.0500.503 Typ 21/650.1	LYMC	39,2	544	640,8	434	56	585	462	14	M 12	28	18	20	4	542.5	545,5	-	505	10,5	-	630	6	105	45,5	-0.5	14,20	28,40	0.5	0,5
231.20.0600.503 Typ 21/750.1	LYMC	47,2	644	742,8	534	56	685	562	16	M 12	32	18	20	4	642,5	645,5	-	605	10,5	-	732	6	122	45,5	- 0,6	14,20	28,40	0,5	0,5
231.20.0700.503 Typ 21/850.1	LYMC	53,1	744	838,8	634	56	785	662	18	M 12	32	18	20	4	742,5	745,5	-	705	10,5	-	828	6	138	45,5	- 0,6	14,20	28,40	0,5	0,5
231.20.0800.503 Typ 21/950.1	LYMC	64,7	844	950,4	734	56	885	762	18	M 12	36	18	20	4	842.5	845,5	-	805	10.5	-	936	8	117	45,5	-0,8	18,93	37,86	0.5	0,5
231.20.0900.503 Typ 21/1050.1	LYMC	69,1	944	1046,4	834	56	985	862	20	M 12	40	18	20	4	942,5	945,5	-	905	10,5	-	1032	8	129	45,5	- 0,8	18,93	37,86	0.5	0.5
231.20.1000.503 Typ 21/1200.1	LYMC	82,5	1094	l198,4	984	56	1135	1012	22	M 12	40	18	20	4	1092,5	1095,5	-	1055	10,5	-	1184	8	148	45,5	- 0,8	18,93	37,86	0,5	0,5

LYMC BEARING