


ZBL.20. ZBL.30 Light bearing



Type	Brand	Drawing No.	Dimensions					Fixing Holes				Gear Data						Weight [KGS]
			De [mm]	de [mm]	di [mm]	V [mm]	Di [mm]	Fe [mm]	Ne	Fi [mm]	Ni [mm]	m	Z	Dp [mm]	Fz norm	Fz max		
ZBL.20.0314.201-2SPTN	LYMC	Drawing 2	417 -0,10	353	315,5	311 -0,09	225	390	8	275	12	5	47	235	15,58	31,17	21	
ZBL.20.0314.201-1SPTN	LYMC	Drawing 1	418	353	315,5	312.5	225	390	8	275	12	5	47	235	15,58	31,17	21	
ZBL.20.0414.201-1SPTN	LYMC	Drawing 1	518	453	415,5	412.5	325	490	8	375	12	5	67	335	15,58	31,17	28	
ZBL.20.0414.201-2SPTN	LYMC	Drawing 2	517 -0,11	453	415,5	411 -0,10	325	490	8	375	12	5	67	335	15,58	31,17	28	
ZBL.20.0544.201-1SPTN	LYMC	Drawing 1	648	583	545,5	542.5	444	620	10	505	16	6	76	456	18,7	37,4	39	
ZBL.20.0544.201-2SPTN	LYMC	Drawing 2	647 -0,13	583	545,5	541 -0,11	444	620	10	505	16	6	76	456	18,7	37,4	39	
ZBL.20.0644.201-1SPTN	LYMC	Drawing 1	748	683	645,5	642.5	546	720	12	605	18	6	93	558	18,7	37,4	46	
ZBL.20.0644.201-2SPTN	LYMC	Drawing 2	747 -0,13	683	645,5	641-0,13	546	720	12	605	18	6	93	558	18,7	37,4	46	
ZBL.20.0744.201-1SPTN	LYMC	Drawing 1	848	783	745,5	742.5	648	820	12	705	20	6	110	660	18,7	37,4	52	
ZBL.20.0744.201-2SPTN	LYMC	Drawing 2	847 -0,14	783	745,5	741-0,13	648	820	12	705	20	6	110	660	18,7	37,4	52	
ZBL.20.0844.201-1SPTN	LYMC	Drawing 1	948	883	845,5	842.5	736	920	14	805	20	8	94	752	249,3	498,7	63	
ZBL.20.0844.201-2SPTN	LYMC	Drawing 2	947 -0,14	883	845,5	841-0,14	736	920	14	805	20	8	94	752	249,3	498,7	63	
ZBL.20.0944.201-1SPTN	LYMC	Drawing 1	1048	983	945,5	942.5	840	102	16	905	22	22	107	856	249,3	498,7	69	
ZBL.20.0944.201-2SPTN	LYMC	Drawing 2	1047 -0,17	983	945,5	941-0,14	840	102	16	905	22	22	107	856	249,3	498,7	69	
ZBL.20.1094.201-1SPTN	LYMC	Drawing 1	1198	1133	1095,5	1092.5	984	1170	16	1055	24	8	125	1000	249,3	498,7	83	
ZBL.20.1094.201-2SPTN	LYMC	Drawing 2	1197 -0,17	1133	1095,5	1091 -0,17	984	1170	16	1055	24	8	125	1000	249,3	498,7	83	
ZBL.30.0955.200-1SPTN	LYMC	Drawing 4	1100	1017	953,5	956,5	812	1060	30	894	30	10	83	830	50,29	100,58	159	
ZBL.30.0955.201-2SPTN	LYMC	Drawing 3	1098-0,17	1017	953,5	955 -0,14	812	1060	30	994	10	8	83	830	50,29	100,58	159	
ZBL.30.1055.200-1SPTN	LYMC	Drawing 4	1200	1117	1053,5	1056,5	912	1160	30	994	30	10	93	930	50,29	100,58	176	
ZBL.30.1055.201-2SPTN	LYMC	Drawing 3	1198-0,17	1117	1053,5	1055-0,17	912	1160	30	994	30	10	93	930	50,29	100,58	176	
ZBL.30.1155.200-1SPTN	LYMC	Drawing 4	1300	1217	1153,5	1156,5	1012	1260	36	1094	36	10	103	1030	50,29	100,58	192	
ZBL.30.1155.201-2SPTN	LYMC	Drawing 3	1298 -0,20	1217	1153,5	1155-0,17	1012	1260	36	1094	36	10	103	1030	50,29	100,58	192	
ZBL.30.1255.200-1SPTN	LYMC	Drawing 4	1400	1317	1253,5	1256,5	1112	1360	42	1194	42	10	113	1130	50,29	100,58	208	
ZBL.30.1255.201-2SPTN	LYMC	Drawing 3	1398 -0,20	1317	1253,5	1255 -0,20	1112	1360	42	1194	42	10	113	1130	50,29	100,58	208	
ZBL.30.1355.200-1SPTN	LYMC	Drawing 4	1500	1417	1353,5	1356,5	1212	1460	42	1294	42	10	123	1230	50,29	100,58	226	
ZBL.30.1355.201-2SPTN	LYMC	Drawing 3	1498-0,20	1417	1353,5	1355 -0,20	1212	1460	42	1294	42	10	123	1230	50,29	100,58	226	

ZBL.20. ZBL.30 Light bearing

ZBL.30.1455.200-1SPTN	LYMC	Drawing 4	1600	1517	1453,5	1456,5	1312	1560	48	1394	48	10	133	1330	50,29	100,58	243
ZBL.30.1455.201-2SPTN	LYMC	Drawing 3	1598 -0,20	1517	1453,5	1455-0,20	1312	1560	48	1394	48	10	133	1330	50,29	100,58	243

