


Series Q--Internal Gear



QNA

No.	Model	Dimensions			Mounting Dimensions						Structural Dimensions		Gear Data				
		Internal gear		H(mm)	Du(mm)	Dn(mm)	n	Through Hole A	Screw Hole B/C/D		n1	h(mm)	B(mm)	m(mm)	External Gear x=-0.5		
		D(mm)	d(mm)						d1(mm)	T(mm)					De(mm)	z	Weight(kg)
1	QN.315.20	408	224	60	370	260	10	17	M16	24	2	10	40	3	207	70	34
1	QN.315.20A	408	224	60	370	260	10	17	M16	24	2	10	40	4	200	51	35
2	QN.355.20	448	264	60	410	300	10	17	M16	24	2	10	40	3	246	84	39
2	QN.355.20A	448	264	60	410	300	10	17	M16	24	2	10	40	4	240	61	40
3	QN.400.20	493	310	60	455	345	12	17	M16	24	2	10	40	4	288	73	44
3	QN.400.20A	493	310	60	455	345	12	17	M16	24	2	10	40	5	280	57	46
4	QN.450.20	543	360	60	505	395	12	17	M16	24	2	10	40	4	336	85	50
4	QN.450.20A	543	360	60	505	395	12	17	M16	24	2	10	40	5	330	67	52
5	QN.500.20	593	410	60	555	445	14	17	M16	24	2	10	40	5	385	78	55
5	QN.500.20A	593	410	60	555	445	14	17	M16	24	2	10	40	6	378	64	57
6	QN.560.20	656	468	70	618	502	14	17	M16	30	2	10	50	4	440	111	76
6	QN.560.20A	656	468	70	618	502	14	17	M16	30	2	10	50	5	435	88	77
7	QN.630.20	726	538	70	688	572	16	17	M16	30	2	10	50	4	512	129	84
7	QN.630.20A	726	538	70	688	572	16	17	M16	30	2	10	50	5	505	102	86
8	QN.710.20	806	618	70	768	652	18	17	M16	30	2	10	50	5	585	118	97
8	QN.710.20A	806	618	70	768	652	18	17	M16	30	2	10	50	6	582	98	97
9	QN.800.20	896	708	70	858	742	20	17	M16	30	2	10	50	6	672	113	110
9	QN.800.20A	896	708	70	858	742	20	17	M16	30	2	10	50	8	664	84	111
10	QN.800.25	908	694	78	864	736	18	22	M20	36	2	10	58	6	654	110	142
10	QN.800.25A	908	694	78	864	736	18	22	M20	36	2	10	58	8	648	82	142
11	QN.900.25	1008	794	78	964	836	20	22	M20	36	2	10	58	8	744	94	163
11	QN.900.25A	1008	794	78	964	836	20	22	M20	36	2	10	58	10	740	75	162
12	QN.1000.25	1108	894	78	1064	936	24	22	M20	36	2	10	58	8	848	107	178
12	QN.1000.25A	1108	894	78	1064	936	24	22	M20	36	2	10	58	10	840	85	179
13	QN.1000.32	1124	880	90	1074	926	24	24	M22	40	2	10	70	8	832	105	230
13	QN.1000.32A	1124	880	90	1074	926	24	24	M22	40	2	10	70	10	830	84	227
14	QN.1120.32	1244	1000	90	1194	1046	28	24	M22	40	4	10	70	10	940	95	263
14	QN.1120.32A	1244	1000	90	1194	1046	28	24	M22	40	4	10	70	12	936	79	262
15	QN.1250.32	1374	1130	90	1324	1176	32	24	M22	40	4	10	70	10	1070	108	294
15	QN.1250.32A	1374	1130	90	1324	1176	32	24	M22	40	4	10	70	12	1068	90	290
16	QN.1400.32	1524	1280	90	1474	1326	36	24	M22	40	4	10	70	12	1212	102	333
16	QN.1400.32A	1524	1280	90	1474	1326	36	24	M22	40	4	10	70	14	1204	87	336
17	QN.1250.40	1394	1110	102	1336	1164	32	26	M24	45	4	12	80	10	1050	106	388
17	QN.1250.40A	1394	1110	102	1336	1164	32	26	M24	45	4	12	80	12	1044	88	388
18	QN.1400.40	1544	1260	102	1486	1314	36	26	M24	45	4	12	80	12	1188	100	444
18	QN.1400.40A	1544	1260	102	1486	1314	36	26	M24	45	4	12	80	14	1190	86	434
19	QN.1600.40	1744	1460	102	1686	1514	40	26	M24	45	4	12	80	12	1392	117	509
19	QN.1600.40A	1744	1460	102	1686	1514	40	26	M24	45	4	12	80	14	1386	100	511

Series Q--Internal Gear

20	QN.1800.40	1944	1660	102	1886	1714	44	26	M24	45	4	12	80	14	1582	114	576
20	QN.1800.40A	1944	1660	102	1886	1714	44	26	M24	45	4	12	80	16	1568	99	591
21	QN.1600.50	1766	1438	124	1704	1496	40	30	M27	50	4	12	100	12	1368	115	714
21	QN.1600.50A	1766	1438	124	1704	1496	40	30	M27	50	4	12	100	14	1358	98	723
22	QN.1800.50	1966	1638	124	1904	1696	44	30	M27	50	4	12	100	14	1568	113	794
22	QN.1800.50A	1966	1638	124	1904	1696	44	30	M27	50	4	12	100	16	1552	98	818
23	QN.2000.50	2166	1842	124	2104	1896	48	30	M27	50	6	12	100	16	1760	111	891
23	QN.2000.50A	2166	1842	124	2104	1896	48	30	M27	50	6	12	100	18	1746	98	913
24	QN.2240.50	2406	2078	124	2344	2136	54	30	M27	50	6	12	100	16	1984	125	1044
24	QN.2240.50A	2406	2078	124	2344	2136	54	30	M27	50	6	12	100	18	1980	111	1041
25	QN.2500.50	2666	2342	124	2604	2396	60	30	M27	50	6	12	100	18	2250	126	1132
25	QN.2500.50A	2666	2342	124	2604	2396	60	30	M27	50	6	12	100	20	2240	113	1148
26	QN.2500.60	2696	2308	150	2626	2374	60	33	M30	56	6	14	122	18	2214	124	1621
26	QN.2500.60A	2696	2308	150	2626	2374	60	33	M30	56	6	14	122	20	2200	111	1654