


Series 13-Internal Gear



133.134

内齿

Internal Gear

No.	Internal gear DL mm	Dimensions			Mounting Dimensions						Structural Dimensions			Gear data						Gear circumferential force		weight kg
		D mm	d mm	H mm	D1 mm	D2 mm	n	Φ mm	dm mm	L mm	n1 mm	H1 mm	h mm	b mm	x	M mm	De mm	z	Normalizing Z10°N	Quenching T10°N		
1	133.25.500	634	366	148	598	402	24	18	M16	32	4	10	32	80	0.5	5	337	68	5	6.7	224	
1	134.25.500	634	366	148	598	402	24	18	M16	32	4	10	32	80	0.5	6	338.4	57	5	6.7	224	
2	133.25.560	694	426	148	658	462	24	18	M16	32	4	10	32	80	0.5	5	397	80	5	6.7	240	
2	134.25.560	694	426	148	658	462	24	18	M16	32	4	10	32	80	0.5	6	398.4	67	5	6.7	240	
3	133.25.630	764	496	148	728	532	28	18	M16	32	4	10	32	80	0.5	6	458.4	77	6	8	270	
3	134.25.630	764	496	148	728	532	28	18	M16	32	4	10	32	80	0.5	8	459.2	58	6	8	270	
4	133.25.710	844	576	148	808	612	28	18	M16	32	4	10	32	80	0.5	6	536.4	90	6	8	300	
4	134.25.710	844	576	148	808	612	28	18	M16	32	4	10	32	80	0.5	8	539.2	68	6	8	300	
5	133.32.800	964	636	182	920	680	36	22	M20	40	4	10	40	120	0.5	8	595.2	75	12.1	16.7	500	
5	134.32.800	964	636	182	920	680	36	22	M20	40	4	10	40	120	0.5	10	594	60	12.1	16.7	500	
6	133.32.900	1064	736	182	1020	780	36	22	M20	40	4	10	40	120	0.5	8	691.2	87	12.1	16.7	600	
6	134.32.900	1064	736	182	1020	780	36	22	M20	40	4	10	40	120	0.5	10	694	70	12.1	16.7	600	
7	133.32.1000	1164	836	182	1120	880	40	22	M20	40	5	10	40	120	0.5	10	784	79	15.1	20.9	680	
7	134.32.1000	1164	836	182	1120	880	40	22	M20	40	5	10	40	120	0.5	12	784.8	66	15.1	20.9	680	
8	133.32.1120	1284	956	182	1240	1000	40	22	M20	40	5	10	40	120	0.5	10	904	91	15.1	20.9	820	
8	134.32.1120	1284	956	182	1240	1000	40	22	M20	40	5	10	40	120	0.5	12	904.8	76	15.1	20.9	820	
9	133.40.1250	1445	1055	220	1393	1107	45	26	M24	48	5	10	50	150	0.5	12	988.8	83	22.9	31.4	1150	
9	134.40.1250	1445	1055	220	1393	1107	45	26	M24	48	5	10	50	150	0.5	14	985.6	71	22.9	31.4	1150	
10	133.40.1400	1595	1205	220	1543	1257	45	26	M24	48	5	10	50	150	0.5	12	1144.8	96	22.9	31.4	1300	
10	134.40.1400	1595	1205	220	1543	1257	45	26	M24	48	5	10	50	150	0.5	14	1139.6	82	22.9	31.4	1300	
11	133.40.1600	1795	1405	220	1743	1457	48	26	M24	48	6	10	50	150	0.5	14	1335.6	96	26.3	36.6	1520	
11	134.40.1600	1795	1405	220	1743	1457	48	26	M24	48	6	10	50	150	0.5	16	1334.4	84	26.3	36.6	1520	
12	133.40.1800	1995	1605	220	1943	1657	48	26	M24	48	6	10	50	150	0.5	14	1531.6	110	26.3	36.6	1700	
12	134.40.1800	1995	1605	220	1943	1657	48	26	M24	48	6	10	50	150	0.5	16	1526.4	96	26.3	36.6	1700	
13	133.45.2000	2221	1779	231	2155	1845	60	33	M30	60	6	12	54	160	0.5	16	1702.4	107	32.2	44.5	2400	
13	134.45.2000	2221	1779	231	2155	1845	60	33	M30	60	6	12	54	160	0.5	18	1699.2	95	32.2	44.5	2400	
14	133.45.2240	2461	2019	231	2395	2085	60	33	M30	60	6	12	54	160	0.5	16	1926.4	121	32.2	44.5	2400	
14	134.45.2240	2461	2019	231	2395	2085	60	33	M30	60	6	12	54	160	0.5	18	1933.2	108	32.2	44.5	2400	
15	133.45.2500	2721	2279	231	2655	2345	72	33	M30	60	8	12	54	160	0.5	18	2185.2	122	36.2	50.1	2750	
15	134.45.2500	2721	2279	231	2655	2345	72	33	M30	60	8	12	54	160	0.5	20	2188	110	36.2	50.1	2750	
16	133.45.2800	3021	2579	231	2955	2645	72	33	M30	60	8	12	54	160	0.5	18	2491.2	139	36.2	50.1	3400	
16	134.45.2800	3021	2579	231	2955	2645	72	33	M30	60	8	12	54	160	0.5	20	2488	125	36.2	50.1	3400	
17	133.50.3150	3432	2868	270	3342	2958	72	45	M42	84	8	12	65	180	0.5	20	2768	139	45.2	62.6	5000	
17	134.50.3150	3432	2868	270	3342	2958	72	45	M42	84	8	12	65	180	0.5	22	2758.8	126	45.2	62.6	5000	
18	133.50.3550	3832	3268	270	3742	3358	72	45	M42	84	8	258	65	180	0.5	20	3168	159	45.2	62.6	5680	
18	134.50.3550	3832	3268	270	3742	3358	72	45	M42	84	8	258	65	180	0.5	22	3154.8	144	49.8	68.9	5680	
19	133.50.4000	4282	3718	270	4192	3808	80	45	M42	84	8	258	65	180	0.5	22	3116.8	165	49.8	68.9	6470	
19	134.50.4000	4282	3718	270	4192	3808	80	45	M42	84	8	258	65	180	0.5	25	3610	145	56.5	78.3	6470	

Series 13--Internal Gear

20	133.50.4500	4782	4218	270	4692	4308	80	45	M42	84	8	258	65	180	0.5	22	4122.8	188	49.8	68.9	7320
20	134.50.4500	4782	4218	270	4692	4308	80	45	M42	84	8	258	65	180	0.5	25	4110	165	56.5	78.3	7320

