


Series Light Type--Internal Gear



H-062
内齿
Internal Gear

Model DL	Weight kg	Dimensions			Mounting Dimension						Structural dimension						Gear Data					Gear ircumferential force		Clearance	
		D [mm]	de[mm]	H [mm]	D1 mm	D2 mm	n	Φ mm	M [mm]	t	D3 [mm]	d1 [mm]	H1 [mm]	H2 [mm]	Hu [mm]	Ho [mm]	d [mm]	m [mm]	z	k.m [mm]	b [mm]	Allowed [KN]	Max [KN]	Axial	Radial
H-062.20.0414	31	486	326.5	56	460	375	24	13.5	12	20	415.5	412.5	45.5	45.5	10.5	10.5	335	5	67	-0.75	45.5	13.54	27.08	≤0.28	≤0.24
H-062.20.0544	42	616	445.2	56	590	505	32	13.5	12	20	545.5	542.5	45.5	45.5	10.5	10.5	456	6	76	-0.6	45.5	16	32	≤0.30	≤0.26
H-062.20.0644	50	716	547.2	56	690	605	36	13.5	12	20	645.5	642.5	45.5	45.5	10.5	10.5	558	6	93	-0.6	45.5	15.62	31.24	≤0.30	≤0.26
H-062.20.0744	58	816	649.2	56	790	705	40	13.5	12	20	745.5	742.5	45.5	45.5	10.5	10.5	660	6	110	-0.6	45.5	15.32	30.64	≤0.30	≤0.26
H-062.20.0844	69	916	737.6	56	890	805	40	13.5	12	20	845.5	842.5	45.5	45.5	10.5	10.5	752	8	94	-0.8	45.5	20.8	41.6	≤0.30	≤0.26
H-062.20.0944	76	1016	841.6	56	990	905	44	13.5	12	20	945.5	942.5	45.5	45.5	10.5	10.5	856	8	107	-0.8	45.5	20.49	40.98	≤0.30	≤0.26
H-062.20.1094	91	1166	985.6	56	1140	1055	48	13.5	12	20	1095.5	1092.5	45.5	45.5	10.5	10.5	1000	8	125	-0.8	45.5	20.16	40.32	≤0.30	≤0.26