


YRTS Bearings



Type	Brand	Boundary Dimensions [mm]								Fixing Holes [mm]						Number Of Connecting Bolts	Extraction Thread Hole		Number Of PitchesX Angle Of Pitches	Screw Tightening Torque	Basic Load Rating				Limiting Speed	Weight
		Inner ring						Outer ring		Axial		Radial		r/min	Kg											
		d	D	T	H	C	d1	dn	dm	d0	ds	TS	Quantity				d1	Quantity			G	Quantity	*T Quantity	□□	Dynamic load Ca kN	Static load Coa kN
YRTS200	LYMC	200	300	45	30	15	274	215	285	7	11	6.2	46	7	45	2	M8	3	48×7.5°	14	155	840	94	226	1160	9.7
YRTS260	LYMC	260	385	55	36.5	18	345	280	365	9.3	15	8.2	34	9.3	33	2	M12	3	36×10°	34	173	1050	110	305	910	18.3
YRTS325	LYMC	325	450	60	40	20	415	342	430	9.3	15	8.2	34	9.3	33	2	M12	3	36×10°	34	191	1260	109	320	760	25
YRTS395	LYMC	395	525	65	42.5	20	486	415	505	9.3	15	8.2	46	9.3	45	2	M12	3	48×7.5°	34	214	1540	121	390	650	33
YRTS460	LYMC	460	600	70	46	22	560	482	580	9.3	15	8.2	46	9.3	45	2	M12	3	48×7.5°	34	221	1690	168	570	560	45