

Types 16L 16 80



Type	Brand	Track Diameter	Weight	Outer Diameter	Inner Diameter	Overall Height	Outer Bolt Circle Diameter	Inner bolt circle diameter	Bore	Number Of Grease Nipples	Diameter [mm]			Ball Diameter	Permissible axial load*		Permissible Acceleration Or Deceleration	Maximum Bearing Clearances	
		DL [mm]		Da [mm]	Di [mm]	H [mm]	La [mm]	Li [mm]	B		Da 1	O	U		2 Axes kN	More Than 2 Axes kN		Axially [mm]	Radially [mm]
310.16.0300.000 · Type 16L/400	LYMC	320	11	404	236	42	375	260	-	4	-	346	294	16	7.5	-	4	1	0.7
310.16.0400.000 · Type 16L/500	LYMC	40	15	504	336	42	475	360	-	4	-	446	394	16	9	-	4	1	0.7
310.16.0500.000 · Type 16L/650	LYMC	570	20	654	486	42	625	510	-	4	-	596	544	16	15	-	4	1	0.7
310.16.0600.000 · Type 16L/750	LYMC	670	23	754	586	42	725	610	-	4	-	696	644	16	18	-	4	1	0.7
310.16.0700.000 · Type 16L/850	LYMC	770	27	854	686	42	825	710	-	4	-	796	744	16	25	-	4	1	0.7
310.16.0800.000 · Type 16L/950	LYMC	870	30	954	786	42	925	810	-	4	-	896	844	16	30	-	4	1	0.7
310.16.0900.000 · Type 16L/1050	LYMC	970	34	1054	886	42	1025	910	-	4	-	996	944	16	35	-	4	1	0.7
320.16.0400.000 · Type 16/500	LYMC	407.5	17	500	315	48	475	340	-	4	-	434	381	16	18	-	7	1	0.7
320.16.0500.000 · Type 16/650	LYMC	557.5	23	650	465	48	625	490	-	4	-	584	531	16	25	-	7	1	0.7
320.16.0600.000 · Type 16/750	LYMC	657.5	26	750	565	48	725	590	-	4	-	684	631	16	30	-	7	1	0.7
320.16.0700.000 · Type 16/850	LYMC	757.5	30	850	665	48	825	690	-	4	-	784	731	16	35	-	7	1	0.7
320.16.0800.000 · Type 16/950	LYMC	857.5	34	950	765	48	925	790	-	4	-	884	831	16	40	-	7	1	0.7
320.16.0900.000 · Type 16/1050	LYMC	957.5	39	1050	865	48	1025	890	-	4	-	984	931	16	45	-	7	1	0.7
330.16.0500.000 · Type 80/685	LYMC	598.5	38	721	567	80	671	657	-	4	696	-	583	16	35	30	7	1	0.7
330.16.0700.000 · Type 80/880	LYMC	793.5	48	916	762	80	866	852	-	4	891	-	778	16	55	50	7	1	0.7
330.16.0900.000 · Type 80/1000	LYMC	913.5	58	1036	882	80	984	970	-	4	1011	-	898	16	65	60	7	1	0.7
330.16.1000.000 · Type 80/1090	LYMC	1003.5	63	1126	972	80	1074	1060	-	4	1101	-	988	16	70	65	7	1	0.7
330.16.0800.010 · Type 80/880	LYMC	793.5	48	916	762	80	866	852	16	4	891	-	778	16	55	50	7	1	0.7
330.16.1000.010 · Type 80/1090	LYMC	1003.5	63	1126	972	80	1074	1060	18	4	1101	-	988	16	70	65	7	1	0.7