

Types 90 90WA 90S



Type	Brand	Track Diameter	Weight	Outer Diameter	Inner Diameter	Overall Height	Outer Bolt Circle Diameter	Inner bolt circle diameter	Bore	Number Of Grease Nipples	Diameter [mm]			Ball Diameter	Permissible axial load*		Permissible Acceleration Or Deceleration	Maximum Bearing Clearances	
		DL [mm]		Da [mm]	Di [mm]	H [mm]	La [mm]	Li [mm]	B		Da 1	O	U		2 Axles kN	More Than 2 Axles kN		Axially [mm]	Radially [mm]
360.18.0800.000 · Type 90/1000.18	LYMC	894	64	1008	854	90	974	960	-	6	1000	-	885	18	75	70	7	1	0.7
360.20.0800.000 · Type 90/1000.20	LYMC	894	64	1008	854	90	974	960	-	6	1000	-	885	20	90	80	7	1	0.7
360.22.0800.000 · Type 90/1000.22	LYMC	894	64	1008	854	90	974	960	-	6	1000	-	885	22	110	100	7	1	0.7
360.24.0800.000 · Type 90/1000.24	LYMC	894	64	1008	854	90	974	960	-	6	1000	-	885	24	160	140	7	1	0.7
360.18.0900.000 · Type 90/1100.18	LYMC	994	71	1108	954	90	1074	1060	-	6	1100	-	985	18	90	80	7	1	0.7
360.20.0900.000 · Type 90/1100.20	LYMC	994	71	1108	954	90	1074	1060	-	6	1100	-	985	20	110	100	7	1	0.7
360.22.0900.000 · Type 90/1100.22	LYMC	994	71	1108	954	90	1074	1060	-	6	1100	-	985	22	130	120	7	1	0.7
360.24.0900.000 · Type 90/1100.24	LYMC	994	71	1108	954	90	1074	1060	-	6	1100	-	985	24	180	160	7	1	0.7
360.22.1000.000 · Type 90/1200.22	LYMC	1094	79	1208	1054	90	1174	1160	-	6	1200	-	1085	22	160	140	7	1	0.7
360.24.1000.000 · Type 90/1200.24	LYMC	1094	79	1208	1054	90	1174	1160	-	6	1200	-	1085	24	200	180	7	1	0.7
360.22.1100.000 · Type 90/1300.22	LYMC	1194	87	1308	1154	90	1274	1260	-	6	1300	-	1185	22	180	160	7	1	0.7
360.18.0900.010 · Type 90/1100.18	LYMC	994	71	1108	954	90	1074	1060	18	6	1100	-	985	18	90	80	7	1	0.7
360.20.0900.010 · Type 90/1100.20	LYMC	994	71	1108	954	90	1074	1060	18	6	1100	-	985	20	110	100	7	1	0.7
360.22.0900.010 · Type 90/1100.22	LYMC	994	71	1108	954	90	1074	1060	18	6	1100	-	985	22	130	120	7	1	0.7
360.24.0900.010 · Type 90/1100.24	LYMC	994	71	1108	954	90	1074	1060	18	6	1100	-	985	24	180	160	7	1	0.7
360.22.1000.010 · Type 90/1200.22	LYMC	1094	79	1208	1054	90	1174	1160	18	6	1200	-	1085	22	160	140	7	1	0.7
360.22.1100.010 · Type 90/1300.22	LYMC	1194	87	1308	1154	90	1274	1260	18	6	1300	-	1185	24	200	180	7	1	0.7
360.22.0955.010 · Type 90/1100.22 WA	LYMC	994	71	1108	954	90	1074	1060	18	6	1100	-	985	22	130	120	7	0.8	0.6
360.24.0955.010 · Type 90/1100.24 WA	LYMC	994	71	1108	954	90	1074	1060	18	6	1100	-	985	24	180	160	7	0.8	0.6
360.22.1055.010 · Type 90/1200.22 WA	LYMC	1094	79	1208	1054	90	1174	1160	18	6	1200	-	1085	22	160	140	7	0.8	0.6
360.24.1055.010 · Type 90/1200.24 WA	LYMC	1094	79	1208	1054	90	1174	1160	18	6	1200	-	1085	24	200	180	7	0.8	0.6
360.22.1155.010 · Type 90/1300.22 WA	LYMC	1194	87	1308	1154	90	1274	1260	18	6	1300	-	1185	22	180	160	7	0.8	0.6

Types 90 90WA 90S

370.20.0804.000 · Type 90 S/1100	LYMC	880/870	82	1000	834	90	966	952	-	6	987	-	871	20/16	160	160	7	1	0.7
370.20.0904.000 · Type 90 S/1100	LYMC	988/978	92	1108	942	90	1074	1060	-	6	1095	-	979	20/16	200	200	7	1	0.7
370.20.1004.000 · Type 90 S/1200	LYMC	1088/1078	101	1208	1042	90	1174	1160	-	6	1195	-	1079	20/16	200	200	7	1	0.7
370.24.1004.000 · Type 90 S/1200.SP	LYMC	1087/1078	101	1208	1042	90	1174	1160	-	6	1195	-	1079	24/16	200	300	7	1	0.7
370.20.0804.010 · Type 90 S/1100	LYMC	880/870	82	1000	834	90	966	952	18	6	987	-	871	20/16	160	160	7	1	0.7
370.20.0904.010 · Type 90 S/1100	LYMC	988/978	92	1108	942	90	1074	1060	18	6	1095	-	979	20/16	200	200	7	1	0.7
370.20.1004.010 · Type 90 S/1200	LYMC	1088/1078	101	1208	1042	90	1174	1160	18	6	1195	-	1079	20/16	200	200	7	1	0.7
370.24.1004.030 · Type 90 S/1200.SP	LYMC	1088/1078	101	1208	1042	90	1174	1160	18	6	1195	-	1079	24/16	200	300	7	1	0.7

