



Type	Brand	Shaft Diameter (mm)	Main dimensions						Shoulder Height		Basic Load Rating□Radial□		Weight KG
			ID d	OD D	PCD dp	B β	Oil Hole d1	Rmin	ds	Dh	C/kN	Co/kN	
RU28	LYMC	10	10	52	28	8		0.3	24	29.5	2.9	24	0.12
RU42	LYMC	20	20	70	41.5	12	3.1	0.6	37	47	7.35	8.35	0.29
RU66	LYMC	35	35	95	66	15	3.1	0.6	59	74	17.5	22.3	0.62
RU85	LYMC	55	55	120	85	15	3.1	0.6	79	93	20.3	29.5	1
RU124(G)	LYMC	80	80	165	124	22	3.1	1	114	134	33.1	50.9	2.6
RU124X	LYMC	80	80	165	124	22	3.1	1	114	134	33.1	50.9	2.6
RU148(G)	LYMC	90	90	210	147.5	25	3.1	1.5	133	162	49.1	76.8	4.9
RU148X	LYMC	90	90	210	147.5	25	3.1	1.5	133	162	49.1	76.8	4.9
RU178(G)	LYMC	115	115	240	178	28	3.1	1.5	161	195	80.3	135	6.8
RU178X	LYMC	115	115	240	178	28	3.1	1.5	161	195	80.3	135	6.8
RU228(G)	LYMC	160	160	295	227.5	35	6	2	208	246	104	172	11.4
RU228X	LYMC	160	160	295	227.5	35	6	2	208	246	104	172	11.4
RU297(G)	LYMC	210	210	380	297.3	40	6	2.5	272	320	156	281	21.3
RU297X	LYMC	210	210	380	297.3	40	6	2.5	272	320	156	281	21.3
RU445(G)	LYMC	350	350	540	445.4	45	6	2.5	417	473	222	473	35.4
RU445X	LYMC	350	350	540	445.4	45	6	2.5	417	473	222	473	35.4