


10 Series Untoothes standard design



Drawing 1

Drawing Number	Brand	Drawing No.	Dimensions And Weight							Mounting Holes				Load Ratings			
			Outside Diameter, Outer Ring	Outside Diameter, Outer Ring, Spigot	Inside Diameter, Inner Ring	Inside Diameter, Inner Ring, Spigot	Inside Dia Outer Ring	Outside Diameter Inner Ring	Weight	Pitch Arde Diameter Outer Ring	Number Of Holes Outer Ring	Pitch Arde Diameter Inner Ring	Number Of Holes Inner Ring	Static		Dynamic	
			Da [mm]	Daz [mm]	di [mm]	Diz [mm]	Di [mm]	da [mm]	G [kg]	La [mm]	na	Li [mm]	ni	Co rad [kN]	Co ax [kN]	Crad [kN]	Cax [kN]
10-160100/0-08000	LYMC	Drawing 1	180		40		103	97	5	140	6	60	6	51	103	71	61
10-160100/0-08003	LYMC	Drawing 2	180	178	40	42	103	97	5	140	6	60	6	51	103	71	61
10-160200/0-08010	LYMC	Drawing 1	280		140		203	197	10	240	12	160	12	101	207	99	85
10-160200/0-08013	LYMC	Drawing 2	280	278	140	142	203	197	10	240	12	160	12	101	207	99	85
10-160300/0-08020	LYMC	Drawing 1	380		240		303	297	14	340	20	260	20	152	310	117	101
10-160300/0-08023	LYMC	Drawing 2	380	378	240	242	303	297	14	340	20	260	20	152	310	117	101
10-160400/0-08030	LYMC	Drawing 1	480		340		403	397	19	440	24	360	24	203	414	130	112
10-160400/0-08033	LYMC	Drawing 2	480	478	340	342	403	397	19	440	24	360	24	203	414	130	112
10-160500/0-08040	LYMC	Drawing 1	580		440		503	497	24	540	28	460	28	253	517	142	122
10-160500/0-08043	LYMC	Drawing 2	580	578	440	442	503	497	24	540	28	460	28	253	517	142	122
10-200311/0-02002	LYMC	Drawing 3	386		242		315.5	312.5	21	360	20	268	20	192	448	140	140
10-200411/0-02012	LYMC	Drawing 3	486		342		415.5	412.5	29	460	24	368	24	254	592	156	156
10-200541/0-02022	LYMC	Drawing 3	616		472		545.5	542.5	37	590	32	498	32	334	780	173	174
10-200641/0-02032	LYMC	Drawing 3	716		572		645.5	642.5	44	690	36	598	36	395	924	184	185
10-200741/0-02042	LYMC	Drawing 3	816		672		745.5	742.5	52	790	40	698	40	457	1068	194	195
10-200841/0-02052	LYMC	Drawing 3	916		772		845.5	842.5	59	890	40	798	40	519	1212	204	205
10-200941/0-02062	LYMC	Drawing 3	1016		872		945.5	942.5	66	990	44	898	44	580	1356	213	214
10-201091/0-02072	LYMC	Drawing 3	1166		1022		1095.5	1092.5	77	1140	48	1048	48	673	1572	224	225
10-200311/0-02003	LYMC	Drawing 4	386	384.5	242	243.5	315.5	312.5	21	360	20	268	20	192	448	140	140
10-200411/0-02013	LYMC	Drawing 4	486	484.5	342	343.5	415.5	412.5	29	460	24	368	24	254	592	156	156
10-200541/0-02023	LYMC	Drawing 4	616	614.5	472	473.5	545.5	542.5	37	590	32	498	32	334	780	173	174
10-200641/0-02033	LYMC	Drawing 4	716	714.5	572	573.5	645.5	642.5	44	690	36	598	36	395	924	184	185
10-200741/0-02043	LYMC	Drawing 4	816	814.5	672	673.5	745.5	742.5	52	790	40	698	40	457	1068	194	195
10-200841/0-02053	LYMC	Drawing 4	916	914.5	772	773.5	845.5	842.5	59	890	40	798	40	519	1212	204	205
10-200941/0-02063	LYMC	Drawing 4	1016	1014.5	872	873.5	945.5	942.5	66	990	44	898	44	580	1356	213	214
10-201091/0-02073	LYMC	Drawing 4	1166	1164.5	1022	1023.5	1095.5	1092.5	77	1140	48	1048	48	673	1572	224	225
10-250455/0-04010	LYMC	Drawing 5	555		355		457	453	53	515	18	395	18	453	1213	249	289
10-250555/0-04020	LYMC	Drawing 5	655		455		557	553	65	615	20	495	20	553	1480	268	311
10-250655/0-04030	LYMC	Drawing 5	755		555		657	653	76	715	24	595	24	653	1746	284	331
10-250755/0-04040	LYMC	Drawing 5	855		655		757	753	90	815	24	695	24	752	2013	300	349

10 Series Untoothes standard design

10-250855/0-03010	LYMC	Drawing 5	955		755		857	853	101	915	28	795	28	852	2280	316	367
10-250955/0-03020	LYMC	Drawing 5	1055		855		957	953	115	1015	30	895	30	952	2546	328	382
10-251055/0-03030	LYMC	Drawing 5	1155		955		1057	1053	128	1115	30	995	30	1051	2813	340	396
10-251155/0-03040	LYMC	Drawing 5	1255		1055		1157	1153	139	1215	36	1095	36	1151	3080	351	409
10-251255/0-03050	LYMC	Drawing 5	1355		1155		1257	1253	150	1315	42	1195	42	1240	3346	364	424
10-251355/0-03060	LYMC	Drawing 5	1455		1255		1357	1353	163	1415	42	1295	42	1350	3613	374	435
10-251455/0-03070	LYMC	Drawing 5	1555		1355		1457	1453	174	1515	48	1395	48	1450	3879	383	447

